



On-Track Plant

Engineering Conformance Certificate

This certificate is issued in accordance with RIS-1530-PLT Issue 6

NAME OF VEHICLE ACCEPTANCE BODY
SNC-Lavalin Rail & Transit Verification Limited

ACCREDITATION CODE
21

Vehicle Class / Description 009/Aquarius/LTE/0D
Vehicle Owner Aquarius Railroad Technologies Ltd
Issue Date 17 February 2021
Expiry Date 16 February 2028

Vehicle Number(s)
99709 009071-0

First Of Class
99709 009341-7 on certificate 21/0849/17 against RIS-1530-PLT Issue 6.

Authorised by:

David Wass
David Wass
SNC-Lavalin Rail & Transit Verification Limited

OFFICIAL STAMP



Reason for issue and Scope of Work

Certification of upgraded 2-wheel rail trailer.
Serial number: AQ/LTE006.
Assessed for compliance to RIS-1530-PLT, Issue 6.
Expiry date conforms to the requirements of RIS-1530-PLT.

Deviations associated with this certificate

None.

Applicant Copy
SN0201195

Certificate Number: 21/0093/21



On-Track Plant

Previous Certificate Number

IF/1086/13.

Maintenance Plan Details

Aquarius Load Tray Extension Operators Manual AQ0601Z, Issue 2. Dated Sept 2017.

Aquarius Load Tray Extension Maintenance Manual AQ0602Z, Issue 2. Dated 05 Sept 2017.

Limitations of Use

1. It shall only operate inside possessions.
2. In travelling and working modes, the trailer is within Plant gauge, as defined by RIS-1530-PLT.
3. Trailer shall NOT on/off track or work on live conductor rail lines.
4. Trailer may on/off track, travel and work under live OLE in conjunction with a safe system of work as determined and authorised by taking guidance from the requirements of GE/RT8024.
5. If adjacent lines are open to traffic, it shall only be used if a safe system of work has been adopted and taken into account of gauge exceedance.
6. Trailer may NOT activate train operated points.
7. Trailer shall NOT travel or work on track with:
 - Cants greater than 200mm, gradients greater than 1:25 and/or curves less than 80m.
8. The trailer cannot be on/off tracked in laden condition.
9. For on/off tracking, a site specific plan shall be used taking account of the applicable module of Network Rail Infrastructure Plant Manual NR/L2/RMVP/0200.
10. In travelling and working mode the trailer shall be the subject to limitations of the towing vehicle.
11. Trailer shall only be coupled to an RRV approved for towing this type of trailer.
It shall NOT be disconnected from the RRV when on track.
12. Trailer rated capacity of 550kg with payload (490kg) evenly distributed shall not be exceeded.

Supplementary Information

1. Two-wheeled rail trailer (with separate drawbar) to work with compatible RRV.
2. Serial No. AQ/LTE006.
3. The trailer is NOT fitted with brakes.
4. Gross weight: 550kg.
5. Tare weight: 60kg.
6. Maximum speeds (travel and working) not to exceed:
 - 10mph plain line. - 5mph switches and crossings. - 1mph raised check/guard rails.
7. Trailer can be manually lifted from the track in an emergency.
8. It is not a conventional rail trailer or attachment and therefore does not need to comply with COP14.

Authorised by:

David Wass

Applicant Copy

Certificate Number: 21/0093/21

SN0201195

Page 2 of 2